

RH-LED-12-150-8XX-P

ROUND LED HIGH BAY FIXTURE



150W, 120–277V Input, 0–10V Dimming



PRODUCT FEATURES


- IP65 rated, wet location
- Powered by 0–10V dimming LED driver
- Ambient operating temperature: –40°C/–40°F to 45°C/113°F
- LED lifetime: L70 >100,000 hours @ 25°C fixture ambient
- Ring bolt mounting accessory included with safety hanging kit
- 0–10V dimming, 10% minimum
- THD: <20%
- 6' cord for input and dimming wires
- Low optical flicker
- Built-in 4kV surge protection

PERFORMANCE SPECIFICATIONS


Catalog Number	Input Voltage	Wattage	Color Temperature	Lumen Output	CRI	Power Factor	Efficacy	Beam Angle
RH-LED-12-150-840-P	120–277V	150W	4000K	19,500 lm	>82.0	>0.92	130 lm/W	110°
RH-LED-12-150-850-P	120–277V	150W	5000K	19,800 lm	>82.0	>0.92	132 lm/W	110°

PHOTOMETRIC SPECIFICATIONS

ISOCANDELA PLOT



POLAR CANDELA DISTRIBUTION



ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0–30	5,672.4	28.7%
0–40	9,387.5	47.6%
0–60	16,704.7	84.6%
60–90	2,975.0	15.1%
70–100	757.1	3.8%
90–120	17.0	0.1%
0–90	19,679.7	99.7%
90–180	62.2	0.3%
0–180	19,742.0	100%

RH-LED-12-150-8XX-P

ROUND LED HIGH BAY FIXTURE

PHYSICAL SPECIFICATIONS

